

Speed Queen®

Multi-Housing

Coin Operated

ST025

ST030

ST035




Coin Drying Tumbler 25, 30 & 35 lb.

Description

- Fast drying performance
- Concentrated airflow pattern and sealed cylinder rims ensure maximum air utilization and energy savings
- Large, easy to clean lint compartment
- Fewer moving parts means fewer maintenance problems and less wear
- High performance heater box increases energy efficiency reduces drying times and provides more comfortable operating environment

Quantum™



Quantum Display gives customers ease of cycle selection buttons and countdown timer. As a business management tool, Quantum offers owners advanced functions such as special and time-of-day promotional pricing and operational reports including equipment usage data.

Micro-Display (MDC)



This control's digital display can give your laundry a more high-tech look. Our Micro Display Control (MDC) shows vend price, while customers stay informed during operation with its digital cycle countdown. The control also can interface with variety of after market card reader systems.

Manual




This control features variable temperature controls, which allow easy regulation of temperatures to effectively dry delicate fabrics.

Nobody Compares with Speed Queen Quality

- Excellence in design. The cabinet design of our stacks strike the perfect balance of heat, airflow and tumble action. This means it utilizes fewer Btu per pound of water removed - resulting in lower gas bills.
- Easy to install. Compact design and convenient utility connections cut installation costs.
- Solid door. Extra large stainless steel door and heavy duty hinge ensure it can withstand repeated use.



- Durable construction. Innovative finishes, high-quality internal components means years of outstanding performance.
- Large, easy-to-clean lint compartment. Less cleaning, more efficiency and fast drying results.
- Axial airflow. Ensures every bit of heated air passes through load. No energy is wasted and loads receive the most concentrated drying possible. That equates to fastest dry times in industry.



Commercial Built to Last Longer

Specifications

Model	ST025	ST030	ST035
Width - in (mm)	28" (711)	31 1/2" (800)	34 1/2" (876)
Depth - in (mm)	40 7/8" (1038)	46 7/8" (1191)	46 7/8" (1191)
Height - in (mm)	63 7/8" (1622)*	63 7/8" (1622)*	63 7/8" (1622)*
Cylinder Depth - in (mm)	24" (610)	30" (762)	30" (762)
Cylinder Diameter - in (mm)	26 1/2" (673)	26 1/2" (673)	30" (762)
Cylinder Volume - cu. ft. (liters)	7.66 (217)	9.57 (271)	12.27 (347)
Dry Capacity - lb (kg)	25 (11.3)	30 (13.6)	35 (15.9)
Filling Ratio	20:1 = 194)	20:1 = 13.6 kg	20:1 = 17.4 kg
Airflow - CFM (liter/sec)	60 Hz: 500 (212) 50 Hz: 430 (194)	60 Hz: 500 (212) 50 Hz: 430 (194)	60 Hz: 650 (245) 50 Hz: 550 (222)
Energy Data	Gas Models: 64,000 Btu/hr (18.8 kW) Steam Models: At 100 psi (6.9 bar): 3.9 BHP, 135,000 Btu/hr (35.5 kW) At 15 psi (1.0 bar): 2.6 BHP, 90,000 Btu/hr (23.8 kW) Electric Models: 12 kW	Gas Models: 73,000 Btu/hr (18.8 kW) Steam Models: At 100 psi (6.9 bar): 3.9 BHP, 135,000 Btu/hr (35.5 kW) At 15 psi (1.0 bar): 2.6 BHP, 90,000 Btu/hr (23.8 kW) Electric Models: 21 kW	Gas Models: 90,000 Btu/hr (26.4 kW) Steam Models: At 100 psi (6.9 bar): 4.8 BHP, 166,000 Btu/hr (40.2 kW) At 15 psi (1.0 bar): 3.7 BHP, 129,000 Btu/hr (27.8 kW) Electric Models: 24 kW
Electrical Specifications	Gas & Steam Models: 120/208-240/60/1; 2W/3W+G 100/200/60/1; 2W+G 100/200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/240/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 380/400-415/50/3; 3W+G 460-480/60/3; 3W+G Electric Models: 208/60/1; 3W+G 240/60/1; 3W+G 200/60/1; 2W+G 200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 240/60/3; 3W+G 380/50/3; 3W+G 400-415/50/3; 3W+G 460-480/60/3; 3W+G	Gas & Steam Models: 120/208-240/60/1; 2W/3W+G 100/200/60/1; 2W+G 100/200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/240/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 380/400-415/50/3; 3W+G 460-480/60/3; 3W+G Electric Models: 208/60/1; 3W+G 240/60/1; 3W+G 200/60/1; 2W+G 200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 240/60/3; 3W+G 380/50/3; 3W+G 400-415/50/3; 3W+G 460-480/60/3; 3W+G	Gas & Steam Models: 120/208-240/60/1; 2W/3W+G 100/200/60/1; 2W+G 100/200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/240/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 380/400-415/50/3; 3W+G 460-480/60/3; 3W+G Electric Models: 208/60/1; 3W+G 240/60/1; 3W+G 200/60/1; 2W+G 200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 240/60/3; 3W+G 380/50/3; 3W+G 400-415/50/3; 3W+G 460-480/60/3; 3W+G
Plumbing Connections	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT
Net Weight - lb (kg)	299 (135)	331 (150)	361 (164)
Shipping Weight - lb (kg)	332 (151)	364 (165)	394 (179)
Shipping Dimensions - in (mm) W D H	30" (762) 43" (1092) 69" (1753)	30" (762) 43" (1092) 69" (1753)	33" (838) 49" (1245) 69" (1753)
Agency Approvals	Gas: CSA Star, CE Electric: UL _{US} , CE Steam: UL _{US} , CE	Gas: CSA Star, CE Electric: UL _{US} , CE Steam: UL _{US} , CE	Gas: CSA Star, CE Electric: UL _{US} , CE Steam: UL _{US} , CE

At Speed Queen, we're confident that our heavy duty commercial washers and dryers are built better to last longer, that we're offering the following limited warranty to prove it. (+Parts only. Labor not included. See Speed Queen Warranty Bond for specifics.)

- **Through three years+**

- a. Any part of the washer, single and stack dryer or stack washer/dryer.

- **Through five years+**

- a. Topload washer transmission assembly.
- b. Base and cabinet assembly including top, lid and door, against rust from inside out.

- **Life of product+**

- a. Stainless steel washtub (topload washer) or stainless steel inner cylinder (frontload washer).

Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems facilities have been awarded ISO 9001 certification. Features and certifications may vary by model.